

Gulf O Flex
CLAD ▶

Our high-quality rubber insulation solution efficiently safeguards outdoor spaces and mechanical systems. Clad, which is made for a variety of uses, offers dependable thermal insulation with passive energy efficiency and no need for active maintenance. Its flexible, lightweight construction can bear a lot of strain without breaking.

It's resistance to moisture vapor, mold and mildew growth ensures that its applications have a long lifespan, less downtime and continuing efficiency.

Available with or without self-adhesive application.



KEY FEATURES & DETAILS



EASY INSTALLATION

With its aluminum foil lamination, applying insulation is quick and easy. Plus, seamlessly cut, bend, apply and seal the material for various purposes, saving time and cost



UV RESISTANT

Guaranteed to last over 10,000 hours with no crack on surface



SUSTAINABLE

Helps systems utilize less energy, leading to less greenhouse gas emissions. CFC and HCFC free, which means they have 0 ODP (Ozone Depletion Potential)



FIRE RESISTANT

This material is self-extinguishing and has low smoke emission, slowing down or preventing the spread of fire



TECHNICAL DATA SHEET

DESCRIPTION

Gulf O Flex® is Flexible Elastomeric Foam made of Nitrile Butadine Rubber, from thickness 6 mm to 50 mm both in sheet (with or without self-adhesive) and in tube forms. The insulation is then finished with factory applied Clad facing as a finish product, which can be used for external applications. The facing will protect the insulation from UV rays and minor mechanical damages.

TECHNICAL DATA

PRODUCT MECHANICAL PROPERTIES		
Model	GULF O FLEX® CLAD	
Material	FLEXIBLE ELASTOMERIC FOAM (NBR)	
Cell Structure	CLOSED CELL	
Density	50 - 70 Kg/m ³	ASTM C 302- 13 (2022) / BS EN 1602: 2013
Thermal Conductivity (k) at 35 deg C mean temperature	0.0321 W/m-K	ASTM C518 -17
Operating Temperature Range Contact our Technical Team for applications with temperatures below (-)40°C & higher than (+)105°C	-183 °C to +105 °C	ASTM C 534
Water Absorption	0.16 vol%	ASTM C534/C534M-20/ ASTM C 209-2015
Water Vapour Transmission	0.00 Perm - in	ASTM E96 / 96M
Water Vapour Diffusion Resistance Factor (μ)	76,366	BS EN 12086:2013
FOIL PROPERTIES		
Aluminium	20 Microns	400 Microns total.
Glass Fiber Cloth	485 ± 5% GSM	
Tensile Strength	660 N/25mm	ASTM D828
UV Rays	No change	Tested for 10,000 hrs. ASTM G 154-16
REACTION TO FIRE		
Flammability	Self- Extinguishing	
Fire Rating	Part 6- Class O Part 7- Class I	BS 476
	FSI ≤ 25 SDI ≤ 50	ASTM E 84/ UL 723



Note: For available sizes please refer our packing data

APPLICATIONS & INDUSTRIES



HOT AND COLD WATER PLUMBING

Pipework requires insulation to maintain required temperatures. It traps heat for heating systems and slows freezing of pipes for cooling systems.



HVAC DUCTS

As many buildings are airtight and rely on filtered air, the ductwork needs to be insulated to ensure it continues to remove pollutants.



REFRIGERATION LINES

Insulation prevents condensation through blocking water vapor. As the cells are tightly packed in, it prevents a lot from going through. It's primarily used in residential & commercial properties, construction, oil & gas, and automotive industries.



ENGINEERED WITH DURABLE FACING

This insulation is ideal for external applications, providing long-lasting protection with no need for further cladding.



